

HYDRAULIC BREAKERS



WHERE EXPERIENCE COUNTS

THE BEST FRAME FOR YOUR REQUEST

BHL



The easiest way to fix a hydraulic breaker on a backhoe loader. FRD has for each backhoe the right setting.

FLAT TOP



The cheapest solution is to attach the breaker with different systems. With the FT framework easy to grow, you have the base mounting plates for quick-change systems of all kinds

SILENCE



Noise reduction is required in the workplace; you have the beginning of the Silence part of our offered possibilities. The frame is up to 6 DbA quieter than the standard frame

SILENCE



The F9 is only in a LN Frame. The standard or special housing can be made on request.

			F6
Operating weight, FT ¹⁾	kg		365
Operating weight, LN ²⁾	kg		350
Height with rod, FT	mm		1450
Height with rod, LN	mm		1400
Operating pressure	min	MPa	10
	max		16
Oil flow	min	l/min	50
	max		150
Impact rate	min	bpm	650
	max		1600
Impact energy	max		884
Rod diameter Ø	mm		75
Effective length rod	mm		450
Weight rod	kg		21,5
Hose inner dia Ø Press. Return	mm		12
Base machine weight	ton		5,0 - 9,0

¹⁾ Operating weight with top bracket. ²⁾ LN Silent Version = Sound and vibration damping

Specifications subject to change without notice.



F6

EXCAVATOR SIZE 5,0-9,5