

# HYDRAULIC BREAKERS



WHERE EXPERIENCE COUNTS

# THE BEST FRAME FOR YOUR REQUEST

BHL



The easiest way to fix a hydraulic breaker on a backhoe loader. FRD has for each backhoe the right setting.

FLAT TOP



The cheapest solution is to attach the breaker with different systems. With the FT framework easy to grow, you have the base mounting plates for quick-change systems of all kinds

SILENCE



Noise reduction is required in the workplace; you have the beginning of the Silence part of our offered possibilities. The frame is up to 6 DbA quieter than the standard frame

SILENCE



The F9 is only in a LN Frame. The standard or special housing can be made on request.

		F9	
Operating weight, FT <sup>1)</sup>		kg	
Operating weight, <sup>1)</sup> LN <sup>2)</sup>		kg	535
Height with rod, FT		mm	
Height with rod, LN		mm	1595
Operating pressure	min	MPa	12
	max		17
Oil flow	min	l/min	45
	max		150
Impact rate	min	bpm	400
	max		1400
Impact energy	max		1305
Rod diameter Ø		mm	90
Effective length rod		mm	500
Weight rod		kg	35,5
Hose inner dia Ø Press. Return		mm	19
Base machine weight		ton	6 - 12

<sup>1)</sup> Operating weight with top bracket. <sup>2)</sup> LN Silent Version = Sound and vibration damping

Specifications subject to change without notice.



LN



# F9LN

## EXCAVATOR SIZE 6,0-12,0